



RECOMMENDED MINIMUM - MAXIMUM HORIZONTAL LENGTH:  
 MIN. C-L TO C-L OF VERTICALS: 32"  
 MAX. C-L TO C-L OF VERTICALS: 63' 10"

HORIZONTAL TUBE SHOULD HAVE A SUPPORT EVERY 10' CAPABLE OF 150 LBS.

IF THE HORIZONTAL TUBE IS USED UN-CUT IN THE HORIZONTAL, THERE ARE ENOUGH SUPPLIES TO POSITION THE TOP OF THE HORIZONTAL TUBE 12" 4" ABOVE THE DRIVEWAY SURFACE.

TRANSTRAX WITH BAVSONIC 1 on 1 AUDIO  
 04811891 - 10 FT OF HORIZONTAL TUBE  
 04811892 - 20 FT OF HORIZONTAL TUBE  
 04811893 - 30 FT OF HORIZONTAL TUBE  
 04811894 - 40 FT OF HORIZONTAL TUBE  
 04811895 - 50 FT OF HORIZONTAL TUBE  
 04811896 - 60 FT OF HORIZONTAL TUBE

**PROPRIETARY**

THIS DOCUMENTATION AND INFORMATION CONTAINED ARE THE SOLE PROPERTY OF E.F. BAVIS & ASSOC., INC. IT SHALL BE RETURNED UPON REQUEST AND SHALL NOT BE REPRODUCED IN WHOLE OR IN PART, OR DISCLOSED TO ANYONE ELSE, BY USE, WITHOUT WRITTEN CONSENT OF E.F. BAVIS & ASSOC., INC.

**E.F. BAVIS & ASSOCIATES INC.**  
 201 GRANDIN RD.  
 MAINEVILLE, OH 45039

T: 513-677-4000 F: 513-677-0582 E: info@efbavis.com www.efbavis.com

**TRANSTRAX**  
 TYPICAL DIMENSIONS

DATE	05/30/14	BY	M. CRAVEN
SCALE	AS SHOWN	DATE	04/30/08
TYPE	INCHES UNLESS OTHERWISE SPECIFIED	SIZE	A
TITLE	TRANSTRAX TYPICAL DIMENSIONS	DRAWING NO.	TT-TYP
SHEET	1 OF 1		